



FLIR Exx- SERIES

ADVANCED THERMAL IMAGING CAMERAS

SPECIFICATIONS

Model	E54	E76	E86	E96
IR resolution	320 × 240 pixels	320 × 240 pixels	464 × 348 pixels	640 × 480 pixels
Resolution with UltraMax enhancement	—	307,200 pixels	645,888 pixels	1.2 megapixels
MSX [*] image enhancement	Yes: details from visual camera add depth and perspective			
Built-in visual camera	5 MP, fixed focus, with built in LED light			
Thermal sensitivity	<40 mK @ 30°C (86°F)	<30 mK @ 30°C (86°F), 42° lens	<30 mK @ 30°C (86°F), 42° lens	<30 mK @ 30°C (86°F), 42° lens
Temperature range	-20°C to 120°C (-4°F to 248°F); 0°C to 650°C (32°F to 1202°F)	-20°C to 120°C (-4°F to 248°F); 0°C to 650°C (32°F to 1202°F)	-20°C to 120°C (-4°F to 248°F); 0°C to 650°C (32°F to 1202°F); 300°C to 1500°C (572°F to 2732°F)	-20°C to 120°C (-4°F to 248°F); 0°C to 650°C (32°F to 1202°F); 300°C to 1500°C (572°F to 2732°F)
Optional temperature range	—	300°C to 1000°C (572°F to 1832°F)		
Accuracy	±2°C (±3.6°F) or ±2% of the reading			
Focus modes	Manual	Continuous laser distance meter (LDM), one-shot LDM, one-shot contrast, manual		
Digital zoom	1–4x continuous			1–8x continuous
Measurement tools	3 spotmeters in live mode, 1 area meter in live mode	3 spotmeters in live mode, 3 area meters in live mode		
Measurement presets	None, center spot, hot spot, cold spot, 3 spots, hot spot-spot* [†]	None, center spot, hot spot, cold spot, User Presets 1&2		
Available lenses	None (fixed lens)	14°, 24°, 42°, macro (2x)		
Lens identification	—	Automatic (FLIR AutoCal™)		
1-Touch Level/Span	Yes: automatic contrast enhancement			
Laser pointer	Yes			
Laser distance meter	—	Yes		
Area measurement information	—	—	Yes	
On-camera routing software	FLIR Inspection Route™ — enabled			
On-camera report building	Voice annotation and GPS tagging to images and video; on-screen text; sketch on infrared images from touchscreen			
FLIR software integration	FLIR Thermal Studio Suite, FLIR Research Studio			
Radiometric JPEG	Yes			
IR, radiometric, visual video recording	Yes			
IR, radiometric, visual video streaming	Yes, over UVC (radiometric, non-radiometric, visual) and Wi-Fi (non-radiometric, visual)			
Communication modes	USB 2.0, Bluetooth [*] , Wi-Fi, DisplayPort			
Cloud services	FLIR Ignite™ for direct, secure image uploading, organizing, and sharing via Wi-Fi (firmware update required for models purchased prior to 2022)			
METERLINK [*]	Yes via Bluetooth			
Display	640 × 480 pixels (VGA) Dragontrail [*] touchscreen			
Drop-testing	2 m (6.6 ft)			
Battery operation time	>2.5 hours, typical use			

*Hot spot to center spot Delta measurement

Specifications are subject to change. For the most up-to-date specifications, please visit teledyneflir.com.