

CANNON LOAD BANKS, INC.

P ALMETT O, GA. 30268

PHONE 770-463-0504

MODEL L-69-80D

PORT ABLE LOAD BANK

The L-69-80D LOAD BANK is designed to provide a temporary load for field servicing and testing 480V AC and 208V AC three phase, 60HZ generators and inverters. The L-69-80 load bank is air cooled. A 120V AC outlet is required to operate the fans and relays. The load is 100KW at 480V AC and 80KW at 208V AC. This unit will also test 120V AC & 240V AC single phase.

MODEL L-69-80D DIMENSIONS

Length.....22"
Width.....8"
Height.....21"
Weight.....60 lbs.



FEATURES

- Load steps: 12.5, 12.5, 25, 25, 25 KW on three phase 480V AC
- Load steps: 5 or 10, 10, 20, 20, 20 KW on three phase 208V AC
- Load steps: 6.5, 6.5, 13, 13, 13 KW on single phase 240V AC
- Load steps: 1.6, 1.6, 3.2, 3.2, 3.2 KW on single phase 120V AC
- Tests 240V AC three phase, 240V AC single phase and 120V AC single phase
- Plug test pins for connecting test leads
- Cam-Lok connectors
- Meters: Digital Multimeter
- Power indicator lights
- Thermal protection
- Carrying case

WEBSITE: WWW.CANNONLOADBANKS.COM

A-RENT

a-rent.com

(IL) 630.748.8900

(TX) 713.564.8900

sales@a-rent.com