



PFT Series - AC High Voltage Dielectric Test Set

0 – 65 kV AC Power Frequency AC Hipot

PFT-652CM
PFT-652CMF
0 - 65 kV AC, up to 2 kVA

The PFT-652CM and PFT-652CMF are from our popular PFT Series of field portable AC hipot test sets. These hipots provide continuously adjustable AC voltage used for a pass/fail, AC over-voltage withstand test on high voltage apparatus, like switchgear, circuit breakers, reclosers, vacuum bottles, hot sticks, bus duct, and any other apparatus needing an AC test voltage. The PFT Series offers the most field portable, affordable, and easiest to operate AC hipots at this voltage and power. Equipped with a two-range voltmeter, three-range current meter and guard circuit for precise leakage current measurements. For bench-top requirements see the ABT Series. Testing loads that require higher power, see our ALT, FPA, HPA and PAR lines of AC dielectric test sets.

- Convenient two-piece field portable design
- Secondary connected 2 Range Voltmeter: 0 - 32.5 / 65 kV AC
- 3 Range Current Meter: 0 – 1 mA AC with x1, x10, and x100 multipliers
- Fixed overload set to 120% of rated output current
- Transit protected meters prevent meter damage between test sites
- Guard/Ground circuit for accurate leakage current measurement
- 20 ft shielded return cable
- Zero Start and External safety Interlock provisions

Model	PFT-652CM / PFT-652CMF
Input	(PFT-652CM) 120 V, 60 Hz, 15 A (PFT-652CMF) 230 V, 50/60 Hz, 8 A
Output	0-65 kV AC, 2 kVA resistive load 2 kVA capacitive load, up to 30 mA current Output current is reduced at lower voltages
Duty	2 kVA: 1 hour ON, 1 hour OFF 1.5 kVA: continuous
Voltmeter	3.5", scaled 32.5/65 kV AC, ±2% F.S.
Current Meter	3.5", scaled 0-1 mA, ±2% F.S. with range multipliers of x1, x10, x100
Distortion	Less than 5%
Size & Weight (W x D x H)	Control: 16.5 x 10.13 x 10.15 in., 34 lb. (PFT-652CMF, 49 lb.) 420 x 260 x 260 mm, 15kg (PFT-652CMF, 22kg) HV Tank: 12 x 13 x 13.5 in., 50 lb. 310 x 330 x 350mm, 23kg
Output Termination	Top Toroid
Scope of Supply	20ft black ground lead, 20ft shielded return cable, external interlock plug, operations manual, calibration certificate



PFT Series: Other models are available from 10 kVac – 100 kVac, 1 kVA – 3 kVA
Optional Accessories & Upgrades

Hand & Foot Safety Switches



PN 90-405

PN 90-410


Safety Ground Sticks



10 inch PN 88-113

14 inch PN 88-150

Reusable Shipping Cases



HV Section PN 32-0332

Control Section PN 32-0333

Optional Upgrades

Digital Metering – Add Suffix “D” · Fault Burn Reactor – PN PFT-BC

HVI HIGH VOLTAGE, INC. 31 County Route 7A • Copake, NY 12516
hvinc.com • f. 518.329.3271 • p. 518.329.3275

AMERICAN MADE IN THE USA
CE
ISO 9001:2015 Certified

A-RENT

a-rent.com

(IL) 630.748.8900

(TX) 713.564.8900

sales@a-rent.com