



DC Hipot Megohmmeter

Combination Units

Two HV Portable DC Test Sets for the Price of One!



PTS-75 Model
(0-75 kVdc, 10mA)



PTS-130 Model
(0-130 kVdc, 10mA)



PTS-200 Model
(0-200 kVdc, 5mA)

Description

The PTS Portable DC Test Set Series of CE marked products are combination high voltage DC proof testers and HV Megohmmeters. Testing for dielectric strength and insulation resistance is now served with one instrument, saving money, size and weight. The PTS series is designed and constructed with field use in mind. It is rugged, reliable and contains all of the features needed for electrical maintenance testing of new or installed electrical apparatus.

Three one piece construction models are available: 37.5 kV, 75 kV and 80kV rated up to 10 mA. Our 100 kV, 130 kV and 200 kV models are designed with separate controls and HV tank. They are fully adjustable and may be used to their full rating for either Hipot or Megohmmeter applications. The PTS series contains numerous features that make it the best Hipot/ Megohmmeter available.

Advantages

Like all High Voltage, Inc. equipment, the PTS series is newly designed, incorporating the latest advances in high voltage technology. No other instrument offers the features, quality and reliability offered here. Several of the many unique advantages include:

- Five range current meter with a 0-1.0 μ A low range for Leakage Current measurements with resolution to 10 nanoamperes
- Megohm readings at any output voltage
- Regulated input for accurate, reliable results. Ideal for field generator use. \pm 1% stability with \pm 10% line change (PTS-37.5 & PTS-75 models)
- Internal HV shorting solenoid with discharge resistor
- Continuous Duty Cycle
- Automatic transit protected meters
- Rugged case with cushion grip handles
- Glass front meters eliminate static buildup

Applications

The PTS Series can be used as a high voltage DC Proof/Hipot tester or as a high voltage Megohmmeter. It is used to proof test or megohm cable insulation, switchgear, motors, transformers, insulators, generators and other electrical apparatus. Its combination Hipot/HV Megohmmeter capability makes it extremely versatile, especially for field testing applications.



ISO 9001 : 2008

HIGH VOLTAGE, INC.

31 County Rt. 7A, Copake, NY 12516 • (518) 329-3275 • Fax: (518) 329-3271
E-Mail: sales@hvinc.com • Web: www.hvinc.com

High Voltage, Inc. designs and manufactures high voltage test equipment for utility and industrial applications. Also available are Very Low Frequency (VLF) high voltage AC test sets, oil dielectric test sets, AC and DC instrumented test sets, cable fault locators and other products.

DC Hipot/Megohmmeter

Combination Units

Features

The following are some of the more outstanding features of the PTS Series:

- Two range voltmeter and five range current meter with a 0-1.0 μ A low range with resolution to 10 nanoamperes
- Output current limited to 10 mA, 5 mA on PTS-200
- Internal HV shorting solenoid with discharge resistor (PTS-37.5 through PTS-130)
- Internal discharge/bleed down resistors on PTS-200
- Automatic transit protected meters
- Insulated Return and Guard circuit to bypass stray and unwanted leakage current
- Rugged case with storage for all input/output leads and ground stick (PTS-37.5 through PTS-80)
- Cable storage bin on HV tank (PTS-100 through PTS-200)
- Surge and transient protection
- External safety and zero start interlocks
- Glass front meters eliminate static buildup



Control Layout

		PTS Model Specifications					
		PTS-37.5	PTS-75	PTS-80	PTS-100	PTS-130	PTS-200*
Input	60 Hz 50/60 Hz	120 V, 5 Amps 230 V, 3 Amps	120 V, 10 Amps 230 V, 5 Amps	120 V, 10 Amps 230 V, 5 Amps	120 V, 10 Amps 230 V, 5 Amps	120 V, 15 Amps 230 V, 8 Amps	120 V, 15 Amps 230 V, 8 Amps
Output		0-37.5 kVdc, 10 mA	0-75 kVdc, 10 mA	0-80 kVdc, 10 mA	0-100 kVdc, 10 mA	0-130 kVdc, 10 mA	0-200 kVdc, 5 mA
Polarity		Negative output. Positive ground.					
Duty		Continuous, capacitive charging.					
Ripple		N/A capacitive load Less than 2.5% RMS resistive load					
Regulation		<1% with 10% input line change capacitive load		N/A (no ferro-resonant regulator)			
Kilovoltmeter		0-15/37.5 kVdc	0-37.5/75 kVdc	0-40/80 kVdc	0-50/100 kVdc	0-75/150 kVdc	0-80/200 kVdc
Current Meter (Megohm Scale)		0-1.0 dc microamperes, w/ x1, x10, x100, x1k, x10k 100-1 Megohms, w/ x0.1, x1, x10, x100, x1k					
Control Dimensions		14w x 11d x 14h 356 mmw x 279 mmd x 356 mmh	14w x 11d x 18h 356 mmw x 279 mmd x 457 mmh	14w x 11d x 18h 356 mmw x 279 mmd x 457 mmh	14w x 11d x 14h 356 mmw x 279 mmd x 356 mmh	14w x 11d x 14h 356 mmw x 279 mmd x 356 mmh	14w x 11d x 14h 356 mmw x 279 mmd x 356 mmh
H.V. Tank Dimensions		Included in Control	Included in Control	Included in Control	9.5w x 11.75d x 14.5h 241 mmw x 298 mmd x 368 mmh	12.5w x 12d x 18h 318 mmw x 305 mmd x 457 mmh	13w x 14.5d x 30.5h 330 mmw x 368 mmd x 775 mmh
Control Weight		50 lbs. (23kg)	68 lbs. (31kg)	62 lbs. (28kg)	30 lbs. (14kg)	34 lbs. (15kg)	34 lbs. (15kg)
Tank Weight (With Cable)					68 lbs. (31kg)	82 lbs. (37kg)	150 lbs. (68kg)
Output Termination		Shielded output cable with clip and boot, 20 ft. (6m)					
Included Cables and Accessories		Input line cord, 10 ft. (3m) Return lead with clip and boot, 20 ft. (6m) Ground lead with clip and boot, 20 ft. (6m) Ground stick with 20 ft. (6m) lead and clip					

Note: For 230 volt line input, an F is suffixed to the model number.

300 kV DC, 5mA and 600 kV DC, 5 mA models available. Please consult the sales dept.

*EPR flexible high voltage x-ray cable is used for the output.



HIGH VOLTAGE, INC.

31 County Rt. 7A, Copake, NY 12516 • (518) 329-3275 • Fax: (518) 329-3271

E-Mail: sales@hvinc.com • Web: www.hvinc.com

High Voltage, Inc. designs and manufactures high voltage test equipment for utility and industrial applications. Also available are Very Low Frequency (VLF) high voltage AC test sets, oil dielectric test sets, AC and DC instrumented test sets, cable fault locators and other products.

A RENT

a-rent.com

(IL) 630.748.8900

(TX) 713.564.8900

sales@a-rent.com